

Complete power, precision and quality

traumadrive™

www.de-soutter.com

traumadrive™

MBU MODULAR ELECTRIC SYSTEM

The De Soutter Medical MBU **traumadrive**[™] is a powerful, modular electric instrument system for small bone and trauma surgery. The handpiece is powered by either sterile or aseptic batteries or by a mains power supply via a low voltage corded module. Li-Ion sterile battery technology assures class leading power to weight ratio.



15000 cpm

See pages 5 and 6 for battery options and corded module.

S88 Extra large type blades

1289664

DBN-470

MBU DRIVES AND ATTACHMENTS

| | Order code | Model | Chuck description | Speed rpm | Cannulation mm | |
|------------------------------------|--|--|---|---|--|--|
| DRILL ATTACHMENT | Γ S 16670 | DU-470 | 0.5 - 4.0 mm (5/32") Keyed | 0 - 1350 | 4.1 | |
| | 16680 | DU-470 DU-470 | 0.5 - 7.4 mm (1/4") Keyed | 0 - 1350 | 4.1 | |
| | 16690 16700 | DU-470 DU-470 | 0.3 - 3.0 mm (1/8") Keyless 0.3 - 7.4 mm (1/4") Keyless | 0 - 1350 0 - 1350 | 3.0 4.2 | |
| QUICK RELEASE DRILLING ATTACHMENTS | | | | | | |
| | 16710 | DU-470 | A.O. Synthes/ASIF | 0 - 1350 | 2.1 | |
| | 16720 16730 19590 20260 | DU-470 DU-470 DU-470 DU-470 DU-470 | Hudson/Zimmer Trinkle DHS/DCS Aesculap | 0 - 1350 0 - 1350 0 - 1350 0 - 1350 0 - 1350 | 4.2 4.2 4.2 4.2 | |
| | 16740 | QU-470 | Medium speed drill ISO 1797 Type 1 | 0 - 4500 | - | |
| HIGH SPEED BUR | 19440 | BU-470 | Low Speed Bur. Uses R Series burs | 0 - 27000 | - | |
| | | | bur guard Order code 18720 Cong bur gua Order code 1 | rd 8730 | Extra long bur guard Order code 18740 | |
| REAMING ATTACHM | IENTS | | | | | |
| | 16750 17750 | RU-470 RU-471 | 0.5 - 7.4 mm (1/4") 0.5 - 7.4 mm (1/4") - non reversible | 0 - 350 0 - 350 | 4.2 4.2 | |
| | 16760 17740 16770 19340 17490 17760 17500 17770 | RU-470 RU-471 RU-470 RU-470 RU-470 RU-471 RU-470 RU-471 | A.O. Synthes A.O. Synthes - non reversible Hudson/Zimmer DHS/DCS Hudson Hudson - non reversible Zimmer Zimmer - non reversible | 0 - 350 0 - 350 | 4.2 4.2 4.2 4.2 4.2 4.2 4.2 4.2 4.2 4.2 | |
| SAWING ATTACHME | NTS | | | | | |
| | 18700 | SU-471 | Button release sagittal saw (non rotating) Uses S86 type blades | 0 - 22000 cpm | - | |
| | 18260 | SU-472 | Button release sagittal saw (rotating) Uses S86 type blades | 0 - 22000 cpm | - | |
| | 16790 | NU-470 | Quick release sagittal saw Uses S88-1XX blades | 0 - 20500 cpm | - | |
| | 19520 | NU-472 | High speed sagittal saw Uses S88-1XX blades | 0 - 24300 cpm | | |
| | 18070 | NU-471 | Quick release sagittal saw Uses S88-4XX blades | 0 - 15000 cpm | - | |
| | 16800 | CU-470 | Small reciprocating saw Uses S92 type blades | 0 - 8000 cpm | • [4] | |
| | 16810 | CU-471 | Large reciprocating saw Uses S22 type blades | 0 - 7000 cpm | · // | |
| PULSE LAVAGE ATTA | | | | | | |
| | 16820 | LU-470 | Pulse lavage attachment Uses P20-7XX series pump kits | 0 - 1350 pulses/min | 7/ | |
| TORQUE LIMITERS | | | | | | |
| | 16860 16870 16880 | TU-404 TU-408 TU-415 | 0.4 Nm 0.8 Nm 1.5 Nm | 0 - 1350 0 - 1350 0 - 1350 | - | |
| RADIOLUCENT DRIL | L ADA | PTOR | | | | |
| | 16830 | TU-470 | Accepts A.O. radiolucent drill attachment Order code 17710 | 0 - 1350 | - | |
| WIRE/PIN DRIVERS | | | | | | |
| 17180 16850 16850 | 17180 16840 16850 | WU-471 WU-470 PU-470 | 0.7 - 4.0 mm capacity 0.6 - 1.8 mm capacity 1.8 - 3.2 mm capacity | 0 - 1350 0 - 1350 0 - 1350 | 4.0 1.8 3.2 | |
| | | | and the second se | | | |

deSouffer MEDICAL Ask for Stericut^ $^{\mbox{\scriptsize B}}$ catalogue for range of sterile packed saw blades, drill bits, rotary burs and K wires.

traumadrive™

BATTERY CHARGERS



BC-700 Battery charger

shown with aseptic batteries.

The BC-700 Battery Charger requires minimal user input. Simply insert battery and the BC-700 will charge, recover and recondition it to its optimum state.

The large touch-screen display with intuitive menu navigation, displays instant battery charge status and condition. It includes a multi-lingual display and other user settings.

The BC-700 also offers a **unique healthcheck facility**, profiling the condition of an individual battery, automatically reconditioning it to provide optimal capacity. Alternatively, a manual healthcheck can be easily selected.

The BC-700 Battery Charger accepts all De Soutter Medical batteries, ensuring total backwards compatibility.



BC-700 MULTI BAY CHARGER AND MODULE OPTIONS

| Charger - Order code | Charger module description | Charger module - Order code | | For battery type | Mains power cordsets 3 metres long. Please specify - Order code. | |
|-------------------------|-----------------------------------|--------------------------------|---|---------------------|--|----------------------|
| 15700 | Without charger module fitted | - | | - | UK | 8290 |
| 16230 | With 4-off CA-703 charger modules | 18120 | | AB-703/AB-704 | Euro US/Canada Australia/New Zealand | 8300 8310 8320 |
| 16220 | With 4-off CA-700 charger modules | 15750 | 2 | SB-703/SB-704 | Swiss | 14700 |

BC-700 charger modules can be quickly and easily changed to suit the batteries being charged.



| Model | Battery type - Order code | For battery type |
|--------|---------------------------|------------------|
| BC-706 | 17990 | SB-703/SB-704 |
| BC-707 | 18000 | AB-703 |
| BC-708 | 18010 | AB-704 |

LITHIUM ION ASEPTIC BATTERIES

Why choose Lithium Ion battery technology

De Soutter Medical Lithium Ion batteries offer the surgical team and sterile services a number of tangible benefits over conventional battery technology.

Key advantages are:

- Li-Ion technology improves battery 'capacity to weight' ratio by around 40% when compared to equivalent NiMH or NiCd chemistries.
- Significantly extends the useable run time of the power tool.
- Eliminates 'memory effect' normally associated with other battery types.
- De Soutter Medical sterile Li-Ion technology readily withstands repeated machine washing and autoclaving.
- Unique **fuel gauge** incorporated within De Soutter Medical Li-Ion batteries allows the surgical team to instantly assess the battery capacity both before and during use.



traumadrive™

LITHIUM ION STERILE BATTERIES



STERILE LITHIUM ION BATTERIES

SMALL BATTERY

| Ÿ | Model | Order code | Voltage | Capacity mAh |
|---------|---------|------------|---------|--------------|
| | SB-703 | 17210 | 13.2V | 1100 |
| LARGE E | BATTERY | | | |
| | Model | Order code | Voltage | Capacity mAh |
| | SB-704 | 17220 | 13.2V | 2500 |

CORDED DIRECT POWER

PS-701 Power supply

Order code 17870

via corded module.

Connected to MBU-470

deSoutte

0

PS-701

New slimline design. Requires no set-up. Simply connect to the CM-700 Corded Module for instant use.

Mains power cordsets 3 metres long. Please specify from options below.

| Order code 8290 |
|------------------|
| Order code 8300 |
| Order code 8310 |
| Order code 8320 |
| Order code 8320 |
| Order code 14700 |
| |

CM-700 Corded module Order code 15720



STERILISATION CONTAINERS



Standard sterile filtered container Order code 19250 PTFE sterile filtered container Order code 19810 Lid gasket -Order code 670023

Half size Sterile Filtered Container Order code 19370 Lid gasket - Order code 669903

PTFE filter cassette Order code 671073 657253

Sterile indicator label pack of 100 Order code 657263



UNITED STATES OF AMERICA De Soutter Medical USA, Inc. 224 Rolling Hill Road, Suite 12A Mooresville, NC 28117 Tel: +1 (704) 655 9040 fax: +1 (704) 987 2035 Email: usa@de-soutter.com

UNITED KINGDOM (INTERNATIONAL HEAD OFFICE) De Soutter Medical Limited Halton Brook Business Park, Weston Road Aston Clinton, Aylesbury, Bucks HP22 5WF Tel: +44 (0) 1296 634 000 Fax: +44 (0) 1296 634 033 Email: info@de-soutter.com

AUSTRALIA

De Soutter Medical Australia Pty Ltd 2/12-14 Apollo Drive, Hallam Victoria 3803 Tel: +61 (0) 3 9702 4441 Fax: +61 (0) 3 9702 4484 Email: australia@de-soutter.com

AUSTRIA

De Soutter Medical Austria Zweigniederlassung Österreich Dietrichsteingasse 10, A-3400 Klosterneuburg Tel: +43 (0) 676 96 71 770 Fax: +43 (0) 2243 21 656 Email: austria@de-soutter.com

BELGIUM

De Soutter Medical Belgium Bessemerstraat 14 3620 Lanaken Tel: +32 (0) 89/47 15 37 Fax: +32 (0) 89/70 12 19 Email: belgium@de-soutter.com FRANCE De Soutter Medical France 1 252 Avenue du Parc des Expositions 33260 La Teste de Buch Tel: +33 (0) 5 56 54 89 36 Fax: +33 (0) 9 70 61 37 60 Email: france@de-soutter.com

GERMANY De Soutter Medical Deutschland Niederlassung Deutschland, Kladenfloss D-66625 Nohfelden Tel: +49 (0) 68 52-99 12 46 Fax: +49 (0) 68 52-99 12 47 Email: deutschland@de-soutter.com

ITALY

De Soutter Medical Italia Località Fornace SNC 27022 Casorate Primo - PV Tel: +39 (0) 2 9009 4098 Fax: +39 (0) 2 9009 2673 Email: italy@de-soutter.com

NETHERLANDS

De Soutter Medical Nederland Gelderlandhaven 2X 3433 PG Nieuwegein Tel: +31 (0) 85 0491480 Fax: +31(0) 85 0491489 Email: nederland@de-soutter.com

deSoutter For further information on De Soutter Medical powered instruments $M \in D \mid C \mid A \mid L$ and cast saw systems please contact the address in your area.